



A new outlook on vital signs — the SureSigns VS2⁺.

Seeing is believing when it comes to the enhanced SureSigns VS2⁺ monitor. With features designed to make taking vital signs easy, the VS2⁺ gives your staff the flexibility and freedom they need to spend more time with their patients. From the easy-to-read viewing area, oversized buttons to the all-new pleth waveform display and intuitive navigation, the VS2⁺ provides the information you need, when you need it, maximizing the time spent at the bedside. And, with wireless capability and data export in HL7 format, the VS2⁺ provides reliability, peace-of-mind — and patient records in record time.



Internal wireless (802.11 a/b/g) optional.

Oral temperature in just four seconds.

Bright, color backlit 4.3" LCD screen.

2D bar-code scanner programmable for multiple ID fields.

Oversized, one-touch NBP on/off button.

NBP modes, including auto intervals, user-defined interval program, and manual start/stop.

Pleth waveform display.

Time-sync network clock.

Confirmation of export records easily seen in green.

Stores up to 100 patient records.

Uses the same supplies as all Philips monitors.

1800 US Hwy 51 N
Woodruff, WI 54568
715-356-0205

SpotMonitor.com
Monitors for Life
An Allied 100 Company

To order visit
SpotMonitor.com
or call **800-920-9919**

PHILIPS
sense and simplicity

Features built around you

LAN/serial data export

in HL7 format.

AC power input

with power cord clip.

Nurse call

output to assist with alarm recognition.

Sturdy handle

and rugged housing for easy portability.

Philips SpO₂ technology

SpO₂ includes a FAST-based

SpO₂ algorithm and is

compatible with a wide

variety of adult, pediatric

and neonatal sensors.

USB port

for easy software upgrades and data export.

Optional integrated strip

recorder for convenient

documentation.

Lithium ion battery.



New premium rollstand includes an easy to clean molded basket which can swivel for easy positioning in tight spaces, and dedicated sections for accessories such as bar code scanner, cleaning wipes, NBP cuffs, extra disposable temperature covers and the SpO₂ sensor.

Product Specifications	
Width, Height, Depth	W: 18.4 cm (8.1"), H: 20.5 cm (7.2"), D: 15.0 cm (5.9")
Weight	2.0 kg (4.3 lbs), including battery, recorder, temperature module and wireless
Screen	10.9 cm (4.3") WQVGA TFT-AM LCD display
NBP	<ul style="list-style-type: none"> Oscillometric using stepwise deflation pressure Adult Measurement Range: <ul style="list-style-type: none"> Systolic: 30–270 mmHg (4.0–36.0 kPa) Diastolic: 10–245 mmHg (1.3–32.7 kPa) MAP: 20–255 mmHg (2.7–34.0 kPa) Pediatric Measurement Range: <ul style="list-style-type: none"> Systolic: 30–180 mmHg (4.0–24.0 kPa) Diastolic: 10–150 mmHg (1.3–20.0 kPa) MAP: 20–160 mmHg (2.7–21.3 kPa) Neonatal Measurement Range: <ul style="list-style-type: none"> Systolic: 30–130 mmHg (4.0–17.0 kPa) Diastolic: 10–100 mmHg (1.3–13.3 kPa) MAP: 20–120 mmHg (2.7–16.0 kPa) NBP Intervals: <ul style="list-style-type: none"> Automatic measurements at intervals of 1, 2, 3, 5, 10, 15, 30, 60, 90 or 120 minutes Up to 1 interval can be defined
SpO ₂	<ul style="list-style-type: none"> Measurement Range: 0%–100% Accuracy: Depends on Sensor
Temperature	<ul style="list-style-type: none"> Modes: Predictive and Monitored Probe Sites: Oral, Rectal or Axillary Range: <ul style="list-style-type: none"> Monitored Mode: 26.7°C–43.3°C (80°F–110°F) Predictive Mode: 34.4°C to 40.6°C (93.9°F–105°F) Accuracy: ±0.1°C (±0.2°F) in Monitored mode
Battery	<ul style="list-style-type: none"> Lithium ion, 10.8–11.1 V, 2150–2300 mAh Operating Time: >4.5 hours, with continuous SpO₂ and NBP interval measured every 15 minutes
Data Output	<ul style="list-style-type: none"> HL7 format, via Ethernet port Serial data
Patient Type	Adult, Pediatric, Neonatal

Also Available	To Order
SureSigns Premium Rollstand	989803176601
SureSigns Standard Rollstand	989803144001
SureSigns Value Rollstand	989803175861
Wall Mount	989803144011
2D Bar Code Reader and Mount	989803147821
Serial Interface Adapter	989803159601
Tabletop Base	989803176261

Ordering Information	
NBP, SpO ₂	863278
• Standard accessories: Adult cuff; NBP tubing; adult finger SpO ₂ sensor, reusable	A01
• No accessories	A02
• Recorder accessories: 5 rolls of recorder paper	R01
• Predictive temperature: Oral temperature probe; 1 box temperature probe covers	T01
NBP, SpO ₂ , Wireless	863279
• Standard accessories: Adult cuff; NBP tubing; adult finger SpO ₂ sensor, reusable	A01
• No accessories	A02
• Recorder accessories: 5 rolls of recorder paper	R01
• Predictive temperature: Oral temperature probe; 1 box temperature probe covers	T01



SureSigns VS2+ has tested compatible with Cisco Compatible Extensions, Version 4. Go to www.cisco.com/go/compatibledisclaimer for complete disclaimer

Please visit www.philips.com/suresigns for more information.



© 2012 Koninklijke Philips Electronics N.V.
All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Philips Healthcare is part of Royal Philips Electronics

www.philips.com/healthcare
healthcare@philips.com

Printed in The Netherlands
4522 962 75751 * JUN 2012