



SureSigns VSi

Vital Signs Monitor Technical Data Sheet

The SureSigns[®] VSi is a vital signs monitor that can measure blood pressure, pulse rate, oxygen saturation (SpO₂), and temperature. The SureSigns VSi vital signs monitor is for measurement of multiple physiological parameters of adults, pediatrics, and neonates in healthcare environments. Additionally, the monitor is intended for use in transport situations within a healthcare facility.

Key Features

- Easy-to-read display with large color-coded numerics
- Lithium ion battery
- Stores up to 50 patient records
- Optional predictive temperature
- Manual stop and start blood pressure measurements
- Available with roll stand, wall mount, or tabletop base mounting options
- HL7 data export via wired LAN, wireless LAN¹, or serial connection
- Easy software upgrades
- Patient ID entry using optional barcode scanner
- Synchronization of the monitor clock when connected to a designated network server

¹ The wireless option may not be available in all countries.

PHILIPS

Main Components

Display

The SureSigns VSi monitor features a color LCD display with a 10.9 cm (4.3 in.) screen.

Front Panel

The following fixed keys and LED indicators are located on the monitor's front panel:


- Alarm Silence
- NBP start/stop
- Main Screen
- Select
- Up/Down
- On/Standby
- AC Power LED
- Charging LED

User Interface

The SureSigns VSi monitor has two display modes: Vital Signs and Patient Records. Press the Main Screen key to switch between the display modes.

Vital Signs Mode

In Vital Signs mode, the main screen displays vital signs measurements for the current patient as numeric values.




Patient Records Mode

In Patient Records mode, the main screen displays the patient records table. You can display all patient records or all records for a specific patient. When highlighted, the patient ID information for the highlighted record appears in a separate pane at the bottom of the screen.

Patient/Type	Date	Time	Pulse	NBP	SpO2	Temp
123432...	A	09/06/11 11:15:00	80 SpO2	120 / 80 (93)	98	--
123432...	A	09/06/11 11:14:00	80 SpO2	120 / 80 (93)	98	--
123432...	A	09/06/11 11:13:43	80 SpO2	-- / -- (--)	98	37.1
123432...	A	09/06/11 11:13:00	80 SpO2	120 / 80 (93)	98	--
123432...	A	09/06/11 11:12:00	80 SpO2	120 / 80 (93)	98	--
123432...	A	09/06/11 11:11:13	80 SpO2	-- / -- (--)	98	37.8
123432...	A	09/06/11 11:10:45	80 SpO2	120 / 80 (93)	98	--

Bottom Bar

The bottom bar contains the following elements:



- Message area
- New Patient button
- System button
- Alarms button
- Battery Status icon
- Date/Time pane

Navigation

Use the Up/Down key to cycle through the screens and menus. Press the Up/Down key until the desired area is highlighted, and then press the Select key to display a new menu, or to select an item.

Mounting Options

The SureSigns VSi monitor has the following mounting options:

- Roll stand
- Wall mount
- Tabletop base

Safety Standards

- EN/IEC 60601-1, EN/IEC 60601-1-2, EN/IEC 60601-2-49, ISO 9919
- Protection class: Class I, internally powered equipment, per IEC 60601-1
- Degree of protection: Type CF defibrillator-proof, per IEC 60601-1
- Ingress of Liquids: IPX1
- Mode of Operation: Continuous
- Protection Against Hazards of Ignition of Flammable Anaesthetic Mixtures: Equipment is not suitable for use in the presence of a flammable anaesthetic mixture with air or oxygen or nitrous oxide, per IEC 60601-1

Wireless Radio Compliance Standards

- ETSI: EN 300 328, EN 301 489, EN 301 893, EN 60950-1
- FCC Regulatory Domain: Part 15.247 Subpart C, Part 15.407 Subpart E
- Industry Canada: RSS-210/RSS-Gen Issue 2

Physical Specifications

Size

- Width: 18.4 cm (8.1 in.)
- Height: 20.5 cm (7.2 in.)
- Depth: 15.0 cm (5.9 in.)
- Weight: 1.7 kg (3.8 lb), including battery, temperature module, and wireless option

Display

- Screen Type: 10.9 cm (4.3 in.) WQVGA TFT-AM LCD display
- Resolution: 480 active pixels/line, 272 active lines per frame
- Refresh frequency: 60 Hz
- Screen active area: 95.0 mm x 53.9 mm (3.7 in. x 2.1 in.)
- Pixel size: 0.213 mm
- Viewing angle: $\pm 60^\circ$

Alarm Audio Range

Meets IEC 60601-2-49 (45 dB to 85 dB)

System Response Time

1 second

Environmental Specifications

Mechanical Shock

Complies with mechanical shock requirement in ISO 9919 standards for use within the healthcare facility. Test conditions include:

- Peak Acceleration: 150 m/s^2 (15.3 g)
- Duration: 11 ms
- Pulse shape: Half sine
- Number of shocks: 3 shocks per direction per axis (18 total)

Electromagnetic Compatibility

Meets the EN 60601-1-2:2001 standard

Mechanical Vibration

Complies with mechanical vibration requirement in ISO 9919 standards for use within the healthcare facility. Test conditions include:

- Frequency range: 10 Hz to 2000 Hz
- Resolution: 10 Hz
- Acceleration amplitude:
 - 10 Hz to 100 Hz: $1.0 \text{ (m/s}^2\text{)}^2/\text{Hz}$
 - 100 Hz to 200 Hz: -3.0 dB/octave
 - 200 Hz to 2000 Hz: $0.5 \text{ (m/s}^2\text{)}^2/\text{Hz}$
- Duration: 10 minutes per each perpendicular axis (3 total)

Thermal

- Operating temperature: 10°C to 40°C (50°F to 104°F)
- Storage temperature:
 - -20°C to 50°C (-4°F to 122°F) for the device
 - -20°C to 40°C (-4°F to 104°F) for the device plus accessories

Humidity

- Operating: Up to 80% RH, non-condensing
- Storage: Up to 90% RH, non-condensing

Altitude

Up to 3000 m (9842 ft) above sea level (701 mbar)

Electrical Specifications

- Internal battery: Lithium ion, smart battery 10.8 V to 11.1 V, 2150 mAh to 2300 mAh
- Battery operating time (new, fully-charged battery): >4.5 hours, taking 20 NBP and SpO₂ measurements every 4 hours
- Battery charge time
 - Up to 5 hours to charge to 90% level when monitoring SpO₂ and taking an NBP measurement every 15 minutes
 - Up to 4 hours to charge to 90% level when the device is in Standby mode
- Internal power supply: 100 VAC to 240 VAC
- Power consumption: < 75 Watts
- Frequency: 50/60 Hz

Application Features

Alarms

- Support for technical alarms only (physiological alarms not supported)
- Two alarm severity levels (high and low) that determine the monitor's visual and audio response
- Visual alarm indicators, including flashing numeric panes and alarm messages
- Audible alarms, configurable for volume and silence

Interface Connections

- Nurse Call Alarm Output
 - Connector: 3.5 mm insulated phone jack, N.O and N.C contacts
 - Contact rating: $\leq 1A @ < 25 VAC$ and $\leq 1A < 60 VDC$
 - Isolation: 1.5 kV
 - Delay time: < 0.5 sec
- Data output
 - Ethernet port
 - USB port, with the optional Serial Interface Adapter
 - Wireless
- Software Upgrade: USB port
- Barcode scanner connection: USB port

Measurement Specifications

SpO₂

- Measurement range
 - SpO₂: 0% to 100%
 - Pulse rate: 30 bpm to 300 bpm
- SpO₂ accuracy: 70% to 100%
 - Philips reusable sensors
 - ± 2% - M1191B, M1191BL, M1192A
 - ± 3% - M1193A, M1194A, M1195A, M1196A, M1196S, M1191T, M1192T, M1196T
 - ± 4% - M1193T (Neonatal)
 - Philips disposable sensors
 - ± 3% - M1131A, M1133A, M1134A (Neonatal)
 - ± 2% - M1132A, M1133A, M1134A (Adult/infant)
 - Nellcor disposable sensors¹
 - ± 3% - M1901B, M1902B, M1903B, M1904B
- Pulse rate accuracy: 2% or 1 bpm, whichever is greater
- Wavelength range: 500 nm to 1000 nm for all specified sensors
- Maximum optical output power: ≤ 15 mW for all specified sensors

Temperature

- Measurement Range
 - Monitored mode: 26.7°C to 43.3°C (80°F to 110°F)
 - Predictive mode: 34.4°C to 40.6°C (93.9°F to 105°F)
- Accuracy: $\pm 0.1^\circ C$ ($\pm 0.2^\circ F$) in Monitored mode
- Resolution: 0.1°C (0.2°F)

Non-invasive Blood Pressure (NBP)

- Technique: Oscillometric using stepwise deflation pressure
- Adult measurement range
 - Systolic: 30 mmHg to 270 mmHg (4.0 kPa to 36.0 kPa)
 - Diastolic: 10 mmHg to 245 mmHg (1.3 kPa to 32.7 kPa)
 - MAP: 20 mmHg to 255 mmHg (2.7 kPa to 34.0 kPa)
 - Pulse rate range: 40 bpm to 300 bpm
- Pediatric measurement range
 - Systolic: 30 mmHg to 180 mmHg (4.0 kPa to 24.0 kPa)
 - Diastolic: 10 mmHg to 150 mmHg (1.3 kPa to 20.0 kPa)
 - MAP: 20 mmHg to 160 mmHg (2.7 kPa to 21.3 kPa)
 - Pulse rate range: 40 bpm to 300 bpm
- Neonatal measurement range
 - Systolic: 30 mmHg to 130 mmHg (4.0 kPa to 17.0 kPa)
 - Diastolic: 10 mmHg to 100 mmHg (1.3 kPa to 13.3 kPa)
 - MAP: 20 mmHg to 120 mmHg (2.7 kPa to 16.0 kPa)
 - Pulse rate range: 40 bpm to 300 bpm
- Blood pressure accuracy
 - Maximum Standard Deviation: 8 mmHg
 - Maximum Mean Error: ± 5 mmHg
- Pulse rate accuracy²
 - 40 bpm to 100 bpm: ± 5 bpm
 - 101 bpm to 200 bpm: $\pm 5\%$ of reading
 - 201 bpm to 300 bpm $\pm 10\%$ of reading
- Initial cuff inflation
 - Adult: 160 mmHg (21.3 kPa)
 - Pediatric: 140 mmHg (18.7 kPa)
 - Neonatal: 100 mmHg (13.3 kPa)

Wireless Interface

- Optional wireless interface
- Networking Standards: IEEE 802.11a, 802.11b, 802.11d, 802.11g, and 802.11h
- Wi-Fi Transmit Power Settings³:
 - 802.11a: 15 dBm (30 mW), 13 dBm (20 mW), 10 dBm (10 mW)
 - 802.11b: 18 dBm (63 mW), 17 dBm (50 mW), 15 dBm (30 mW), 13 dBm (20 mW), 10 dBm (10 mW), 7 dBm (5 mW), 0 dBm (1mW)
 - 802.11g: 18 dBm (63 mW), 17 dBm (50 mW), 15 dBm (30 mW), 13 dBm (20 mW), 10 dBm (10 mW), 7 dBm (5 mW), 0 dBm (1mW)
- Security Standards:
 - WEP, WPA, and WPA2
 - 802.1X Extensible Authentication Protocol Type: PEAP-MSCHAPv2, EAP-TLS

² The pulse rate value derived from NBP is an averaged value.

³ Maximum transmit power varies according to individual country regulations. All values nominal +/- 2 dBm.

¹ The Nellcor disposable sensors are only available from Philips in Europe and Japan.

- Typical Receiver Sensitivity¹:
 - 802.11a: (6 Mbps -85 dBm, 9 Mbps -83 dBm, 12 Mbps -83 dBm, 18 Mbps -81 dBm, 24 Mbps -75 dBm, 36 Mbps -73 dBm, 48 Mbps -68 dBm, 54 Mbps -67 dBm (PER <= 10%))
 - 802.11b: (1 Mbps -95 dBm, 2 Mbps -94 dBm, 5.5 Mbps -93 dBm, 11 Mbps -89 dBm (PER <= 10%))
 - 802.11g: (6 Mbps -93 dBm, 12 Mbps -88 dBm, 18 Mbps -85 dBm, 24 Mbps -83 dBm, 36 Mbps -77 dBm, 48 Mbps -74 dBm, 54 Mbps -72 dBm (PER <= 10%))
- Antenna: The antenna in the monitor has the following specifications:
 - Form Factor: Whip
 - Type: Dipole
 - Maximum 2.4 GHz Gain: 2.15 dBi
 - Maximum 5.0 GHz Gain: 3.90 dBi

Ordering Information

863275

Standard: NBP

Option	Accessories
A01	Standard accessories include: <ul style="list-style-type: none"> • Adult cuff • NBP tubing, 3 m long
A02	No accessories included with monitor.

¹ All values nominal to +/- 3 dBm.

863276

Standard: NBP, SpO₂

Monitor options: Predictive temperature

Option	Accessories
A01	Standard accessories include: <ul style="list-style-type: none"> • Adult cuff • NBP tubing, 3 m long • Adult finger SpO₂ sensor, reusable
A02	No accessories included with monitor.
T01	Predictive temperature accessories include: <ul style="list-style-type: none"> • Oral temperature probe • 1 box of temperature probe covers

863277

Standard: NBP, SpO₂, Predictive temperature, Wireless

Option	Accessories
A01	Standard accessories include: <ul style="list-style-type: none"> • Adult cuff • NBP tubing, 3 m long • Adult finger SpO₂ sensor, reusable • Oral temperature probe • 1 box of temperature probe covers
A02	No accessories included with monitor.

SureSigns Accessories

SpO₂ Accessories

Philips Reusable Sensors	
M1191B	Adult finger
M1192A	Pediatric/small adult finger
M1193A	Neonatal foot/hand
M1194A	Adult ear clip
M1195A	Infant finger
M1196A	Adult finger clip (long cable)
M1196S	Adult/large pediatric finger clip
M1191BL	Adult finger (long cable)
M1191T	Adult finger clip
M1192T	Pediatric finger clip
M1193T	Neonatal foot/hand
M1196T	Pediatric/small adult finger clip

Philips Disposable Sensors	
M1131A	Adult finger
M1132A	Infant digit
M1133A	Neonatal/infant/adult: Foot/hand sensor for neonate, big toe/thumb for infant, finger for adult.
M1134A	Neonatal/infant/adult: Foot/hand sensor for neonate, big toe/thumb for infant, finger for adult.

Nellcor Disposable Sensors ^a	
M1904B	Adult digit
M1903B	Pediatric digit
M1902B	Infant digit
M1901B	Neonate foot, adult digit

^a The Nellcor disposable sensors are only available from Philips in Europe and Japan.

SpO ₂ Extension and Adapter Cables	
M1020-61100	3.6 m LNOP adapter cable for Masimo sensors
989803148221	3 m LNCS adapter cable for Masimo sensors
M1941A	2 m extension cable for Philips reusable sensors
M1943A	1.1 m adapter cable for Philips and Nellcor disposable sensors
M1943AL	3 m adapter cable for Philips and Nellcor disposable sensors

NBP Accessories

Reusable Comfort Cuffs	
M1576A	Thigh
M1575A	Large adult
M1574A	Adult
M1573A	Small adult
M1572A	Pediatric
M1571A	Infant
M1598B	Interconnect tubing, 1.5 m
M1599B	Interconnect tubing, 3 m

Reusable Traditional Cuffs	
40401E	Thigh
40401D	Large adult
40401C	Adult
40401B	Pediatric
40401A	Infant
M1598B	Interconnect tubing, 1.5 m
M1599B	Interconnect tubing, 3 m

Reusable Easy Care Adult/Pediatric Cuffs	
M4559B	Thigh
M4558B	Large adult, X-long
M4557B	Large adult
M4556B	Adult, X-long
M4555B	Adult
M4554B	Small adult
M4553B	Pediatric
M4552B	Infant
M1598B	Interconnect tubing, 1.5 m
M1599B	Interconnect tubing, 3 m

Disposable Soft Adult/Pediatric Cuffs	
M4579B	Thigh
M4578B	Large adult, X-long
M4577B	Large adult
M4576B	Adult, X-long
M4575B	Adult
M4574B	Small adult
M4573B	Pediatric
M4572B	Infant
M1598B	Interconnect tubing, 1.5 m
M1599B	Interconnect tubing, 3 m

Disposable Adult/Pediatric Cuffs	
M1879A	Thigh
M1878A	Large adult
M1877A	Adult
M1876A	Small adult
M1875A	Pediatric
M1874A	Infant
M1598B	Interconnect tubing, 1.5 m
M1599B	Interconnect tubing, 3 m

Disposable Neonatal Cuffs (Luer Connector) ^a	
M1866A	Size 1
M1868A	Size 2
M1870A	Size 3
M1872A	Size 4
M1596B	Interconnect tubing, 1.5 m
M1597B	Interconnect tubing, 3 m

a The Luer connector cuffs and air hoses are not available in EEA (European Economic Area) countries.

Disposable Neonatal Cuffs (Safety Connector) ^a	
M1866B	Size 1
M1868B	Size 2
M1870B	Size 3
M1872B	Size 4
M1873B	Size 5 Infant
M1596C	Interconnect tubing, 1.5 m
M1597C	Interconnect tubing, 3 m

a The safety connector cuffs and air hoses may not be available in all countries. Check with your local sales organization.

Disposable Soft Neonatal Cuffs (Safety Connector)	
M1866S	Size 1
M1868S	Size 2
M1870S	Size 3
M1872S	Size 4
M1873S	Size 5 Infant
M1596C	Interconnect tubing, 1.5 m
M1597C	Interconnect tubing, 3 m

Temperature Accessories

Part Number	Accessory
989803143391	Rectal probe well and kit (all patient types)
989803143381	Oral/Axillary probe and well kit
M4823A	Disposable probe covers, 1000 per case

Miscellaneous Accessories

Part Number	Accessory
989803144001	Roll Stand with Basket
989803144011	Wall Mount
989803174881	Lithium Ion Battery
989803167691	1D Barcode Scanner (includes mounting arm for use with roll stand)
989803147821	2D Barcode Scanner (includes mounting arm for use with roll stand)
989803159601	Serial Interface Adapter
989803148841	Cable Management Kit
989803150281	SureSigns Mount Adapter
453564039661	USB Hub, 4-port
989803176261	SureSigns VS1 and VS2 ⁺ Tabletop Base

**Philips Healthcare is part of
Royal Philips Electronics**

How to reach us

www.philips.com/healthcare
healthcare@philips.com
fax: +31 40 27 64 887

Asia
+852 2821 5888

Europe, Middle East, Africa
+49 7031 463 2254

Latin America
+55 11 2125 0744

North America
+1 425 487 7000
800 285 5585 (toll free, US only)



The SureSigns VSi vital signs monitor is a Class IIb device and complies with the requirements of the Council Directive 93/42/EEC of 14 June 1993 (Medical Device Directive).



The radio device used in the SureSigns VSi vital signs monitor is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC (Radio Equipment and Telecommunications Terminal Equipment Directive).



**1800 US Hwy 51 N
Woodruff, WI 54568
715-356-0205**

SpotMonitor.com
Monitors for Life
An Allied 100 Company

**To order visit
SpotMonitor.com
or call 800-920-9919**

Please visit www.philips.com/



© 2011 Koninklijke Philips Electronics N.V.
All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Printed in The Netherlands.
4522 962 76931 * OCT 2011